

# REINFORCED HOSING (PTY) LTD

## HOSE SPECIFICATIONS

### CSH

#### REH CROP SPRAY HOSE

**Liner Material:** N4530I2050 V/PVC NITRILE  
**Cover Material:** I3050U7 V/PVC BLUE

Specification Requirement CROP SPRAY HOSE	13mm
	Liner max. inside diameter.
Liner min. inside diameter.	12,80
Liner max. wall thickness.	1,60
Liner min. wall thickness.	1,80
Inner Liner max. wall thickness.	1,00
Inner Liner min. wall thickness.	0,80
Number of bobbins. – 2000 Den.	24
Number of bobbins. – 1000 Den	24
Braid Angle - Close	C
Max. Outer Cover thickness.	1,20
Min. Outer Cover thickness.	1,00
Weight per meter in Gms.	290
Weight per 30m roll in Kgs.	8.70
Min. Burst pressure - Bar.	110
Temperature Range - Degrees	-10 to +60

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: March 5, 2021

Issue No: 1

Issuing Officer: T. Niemand

Signature \_\_\_\_\_

*Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.*