

REINFORCED HOSING (PTY) LTD

HOSE SPECIFICATIONS

LPG – SANS 1156-2012

LPG – GAS HOSE

Liner Material: FN631/TQ3 V/PVC
Cover Material: I305007 V/PVC, X4000U1

Specification Requirement LPG	Hose size in millimetres		
	6,3	8	10
Inner Liner max. inside diameter.	6,4	8,2	10,2
Inner Liner min. inside diameter.	6,2	7,9	9,8
Inner Liner max. wall thickness.	1,5	1,7	2,1
Inner Liner min. wall thickness.	1,3	1,6	1,9
Number of yarn plies – 1100 Den.	1	2	2
Number of bobbins.	12	16	16
Max. Outer Cover thickness.	1,2	1,35	1,7
Min. Outer Cover thickness.	1,0	1,2	1,5
Weight per meter in Gms.	105	142	174
Weight per 30m roll in Kgs.	3.15	4.26	5.22
Min. Burst pressure in Kpa.	52	52	52

These Specifications are Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: FEBRUARY 1, 2017

Issue No: 2

Issuing Officer: T. Niemand

Signature _____

Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.