

# REINFORCED HOSING (PTY) LTD

## HOSE SPECIFICATIONS

### RCT20

#### REH Clear Thick Wall Tubing

Material: X4000 Clear V/PVC

Specification Requirement RCT20	Hose size in millimetres											
	3	5	6,3	8	10	12	16	20	25	32	40	50
Max. inside diameter.	3,0	5,0	6,4	8,2	10,2	12,8	16,2	20,2	25,5	32,5	40,5	50,8
Min. inside diameter.	2,9	4,9	6,2	7,9	9,8	12,0	15,8	19,0	24,0	31,6	39,5	49,5
Max. wall thickness.	1,4	1,5	2,0	2,2	2,5	2,6	2,7	2,8	2,8	3,0	3,3	3,5
Min. wall thickness.	1,2	1,3	1,8	2,0	2,3	2,4	2,5	2,6	2,6	2,8	3,1	3,3
Weight per meter in Gms.	25	36	62	85	120	140	185	225	315	430	573	690
Weight per 30m roll Kgs.	0,75	1,08	1,86	2,50	3,60	4,20	4,50	6,75	9,45	12,9	17,2	20,7

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: February 1, 2019

Issue No: 1

Issuing Officer: T. Niemand

Signature \_\_\_\_\_

*Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.*

Spec RCT20.doc