

# REINFORCED HOSING (PTY) LTD

## HOSE SPECIFICATIONS

### RAS

#### Reinforced Antistatic Hose - Ribbed

---

**Liner Material:** A2/8503 V/PVC  
**Cover Material:** FE80/4611 Yellow V/PVC, I3050Y7 V/PVC

Specification Requirement REH 10 YEAR	Hose size in millimetres	
	20mm	25mm
Inner Liner max. inside diameter.	20,00	25,00
Inner Liner min. inside diameter.	19,00	24,00
Inner Liner max. wall thickness.	2,50	2,90
Inner Liner min. wall thickness.	2,20	2,60
Number of yarn plies – 1100 Den.	5	5
Number of bobbins.	24	24
Max. Outer Cover thickness.	2,20	2.30
Min. Outer Cover thickness.	1,90	2,00
Weight per meter in Gms.	600	800
Weight per 30m roll in Kgs.	18,00	24,00
Min. Burst pressure in Kpa.	6000	5600

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: March 1, 2014

Issue No: 1

Issuing Officer: T. Niemand

Signature \_\_\_\_\_

*Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.*