

REINFORCED HOSING (PTY) LTD

HOSE SPECIFICATIONS

RAS

Reinforced Oxygen & Acetylene Hose

Liner Material: X4500U5 PR TQ3 V/PVC
Cover Material: I3050O7 V/PVC, X4000U1

Specification Requirement	Hose size in millimetres		
	6,3mm	8mm	10mm
Inner Liner max. inside diameter.	6,4	8,2	10,2
Inner Liner min. inside diameter.	6,2	7,9	9,8
Inner Liner max. wall thickness.	1,5	1,55	1,50
Inner Liner min. wall thickness.	1,3	1,45	1,50
Number of yarn plies – 1100 Den.	1	1	2
Number of bobbins.	12	16	16
Max. Outer Cover thickness.	1,2	1,35	1,45
Min. Outer Cover thickness.	1,0	1,25	1,35
Weight per meter in Gms.	105	134	155
Weight per 30m roll in Kgs.	3.15	4,02	4,65
Min. Burst pressure in Kpa.	50	50	50

These Specifications are the Standard Requirements for the above product and they are kept, used and controlled by Reinforced Hosing (Pty) Ltd in their Manufacturing and Quality Control process.

Effective Date: February 10, 2016

Issue No: 1

Issuing Officer: T. Niemand

Signature _____

Note: Unless the issuing Signature is in red, this is a photocopy and may not be current.