



WATEX REINFORCED PVC MINING HOSES

COMPLY WITH SANS 1086/2007 AND ARE DESIGNED FOR AFRICAN MINING CONDITIONS AND HAVE A WIDE RANGE OF APPLICATIONS.

WATEX MINING HOSE APPLICATIONS:

- Jack Hammers
- Compressors
- Pneumatic Tools
- Air & Water Conveyance

WATEX MINING HOSES

ARE:

- Excellent Cut & Abrasion Resistant
- Oil & Diesel Resistant
- Lightweight & Flexible
- Withstands Temperatures Ranging from 0° C to 50° C





WATEX Yellow Heavy Duty super flexible mining hose, suitable for colder conditions. Operating temperature -10 $^{\circ}$ C to +50 $^{\circ}$ C.

| PRODUCT CODE: | RMY10030 | RMY12030 | RMY20030 | RMY25030 | RMY32030 | RMY40030 | RMY50030 |
|-----------------------------|----------|----------|----------|----------|----------|----------|----------|
| Nominal ID (mm) | 10 | 12 | 20 | 25 | 32 | 40 | 50 |
| Burst Pressure Kpa | 6800 | 6800 | 6000 | 5600 | 4000 | 3500 | 3500 |
| Working Pressure Kpa | 1700 | 1700 | | | | | |



WATEX Green Heavy Duty super flexible mining hose, suitable for colder conditions. Operating temperature -10° C to $+50^{\circ}$ C.

| operating temperature | operating temperature to a to too or | | | | | | | | | | |
|-----------------------------|--------------------------------------|----------|----------|----------|----------|----------|----------|--|--|--|--|
| PRODUCT CODE: | RMG10030 | RMG12030 | RMG20030 | RMG25030 | RMG32030 | RMG40030 | RMG50030 | | | | |
| Nominal ID (mm) | 10 | 12 | 20 | 25 | 32 | 40 | 50 | | | | |
| Burst Pressure Kpa | 6800 | 6800 | 6000 | 5600 | 4000 | 3500 | 3500 | | | | |
| Working Pressure Kpa | 1700 | 1700 | 1500 | 1400 | 1000 | 900 | 900 | | | | |



WATEX Blue Heavy Duty super flexible mining hose, suitable for colder conditions. Operating temperature -10° C to $+50^{\circ}$ C.

| alterna 2 to leave a to a to a | | | | | | | | | | | |
|--------------------------------|----------|----------|----------|----------|----------|----------|----------|--|--|--|--|
| PRODUCT CODE: | RMB10030 | RMB12030 | RMB20030 | RMB25030 | RMB32030 | RMB40030 | RMB50030 | | | | |
| Nominal ID (mm) | 10 | 12 | 20 | 25 | 32 | 40 | 50 | | | | |
| Burst Pressure Kpa | 6800 | 6800 | 6000 | 5600 | 4000 | 3500 | 3500 | | | | |
| Working Pressure Kpa | 1700 | 1700 | 1500 | 1400 | 1000 | 900 | 900 | | | | |



WATEX Orange Heavy Duty super flexible mining hose, suitable for colder conditions.

Operating temperature -10° C to +50° C.

| oporumny component | operating terriporating to the root of | | | | | | | | | |
|-----------------------------|--|----------|----------|----------|----------|----------|----------|--|--|--|
| PRODUCT CODE: | RM010030 | RM012030 | RM020030 | RM025030 | RM032030 | RM040030 | RM050030 | | | |
| Nominal ID (mm) | 10 | 12 | 20 | 25 | 32 | 40 | 50 | | | |
| Burst Pressure Kpa | 6800 | 6800 | 6000 | 5600 | 4000 | 3500 | 3500 | | | |
| Working Pressure Kpa | 1700 | 1700 | 1500 | 1400 | 1000 | 900 | 900 | | | |



WATEX-MRD Red Rockdrill Hose. Heavy Duty Ultra High Pressure Hose.

Operating temperature -0° C to +50° C.

| operating temperature | operating temperature of the record | | | | | | | | | | |
|-----------------------------|-------------------------------------|----------|---|----------|---|---|----------|--|--|--|--|
| PRODUCT CODE: | | MRD12030 | | MRD25030 | | | MRD50030 | | | | |
| Nominal ID (mm) | - | 12 | - | 25 | - | - | 50 | | | | |
| Burst Pressure Kpa | - | 10000 | - | 8000 | - | - | 4500 | | | | |
| Working Pressure Kpa | - | 3000 | - | 2000 | - | - | 1125 | | | | |



| ı | |
|---|-----------------------------------|
| ı | WATEX - Anti-Static Loading Hose. |
| ı | WATEX - Anti-Static Loading Hose |
| | |

Anti-Static and Semi conductive, complies with SANS 2878:2011

| PRODUCT CODE: | RMA16030 | RMA20030 |
|---------------------------|--------------------------------|--------------------------------|
| Description | Nominal Internal Diameter (mm) | Nominal Internal Diameter (mm) |
| ATS - Smooth ID | 16 | 20 |
| OD | 24 Max | 29 Max |
| ATR - Ribbed (Heavy Duty) | 20 | 25 |

WATEX PVC INDUSTRIAL HOSES

GOOD FLEXIBILITY, HIGH BURST AND WORKING PRESSURES AND A GOOD RESISTANCE TO FUELS, GASSES AND CHEMICALS.



| -1 | WATEX Clear Wall Tubing – Low pressure applications such as laboratory, instruments, fish tanks and fountain tubing. Chemical resistant*. Good clarity. | | | | | | | | | | |
|----|---|--------|--------|--------|--------|---------|---------|---------|---------|---------|---------|
| ď | Nominal ID mm | 3 | 5 | 6,3 | | 10 | 12,5 | 16 | 20 | 25 | 32 |
| 1 | Wall Thickness | | | | | | | | | | |
| I | PRODUCT CODE: | CT300 | CT500 | CT600 | CT800 | CT1000 | CT1200 | | | | |
| | CT – Thin Wall | 0,8 | 0,9 | 1 | 1 | 1,2 | 1,3 | - | - | - | - |
| | PRODUCT CODE: | CTH300 | CTH500 | CTH600 | CTH800 | CTH1000 | CTH1200 | CTH1600 | CTH2000 | CTH2500 | CTH3200 |
| I | CTH – Thick Wall | 1,4 | 1,5 | 2 | 2,2 | 2,5 | 2,6 | 2,7 | 2,7 | 3 | 3,1 |



| WATEX Clear Reinforced Tubing - High pressure applications such as air, water and diluted acids and oils. | | | | | | | | | | |
|---|--------|---------------|---------------------------------|--------|---------|---------|---------|---------|---------|---------|
| Chemical resistant*. Good clarity. | | | Fish tanks and fountain tubing. | | | | | | | |
| PRODUCT CODE: | CRT300 | CRT500 | CRT600 | CRT800 | CRT1000 | CRT1200 | CRT1600 | CRT2000 | CRT2500 | CRT3200 |
| Nominal ID mm | 3 | 5 | 6,3 | 8 | 10 | 12,5 | 16 | 20 | 25 | 32 |
| Nominal OD mm | 7 | 9 | 12 | 13 | 15 | 19 | 24 | 28 | 34 | 42 |
| Working Pressure Kpa | 1700 | 1500 | 1300 | 1200 | 1100 | 1100 | 1000 | 1000 | 1000 | 900 |
| Burst Pressure Kpa | 7000 | 6600 | 5900 | 5200 | 4500 | 4200 | 4000 | 4000 | 4000 | 3800 |

^{*} Refer to PVC Chemical Resistant Chart



| WATEX Fuel Reinforced Hose – Transparent blue for petrol, diesel, oil and chemicals*. Good clarity. | | | | | | | | | | |
|--|--------|--------|--------|--------|---------|---------|--|--|--|--|
| PRODUCT CODE: | CRF300 | CRF500 | CRF600 | CRF800 | CRF1000 | CRF1200 | | | | |
| Nominal ID (mm) | 3 | 5 | 6,3 | 8 | 10 | 12,5 | | | | |
| Nominal OD (mm) | 7 | 9 | 12 | 13 | 15 | 19 | | | | |
| Working Pressure Kpa | 1700 | 1500 | 1300 | 1200 | 1100 | 1100 | | | | |
| Burst Pressure Kpa | | | | | | | | | | |





| WATEX-RMO Orange Standard Duty LPG Gas Hose. (PR NITRILE) | | | | | | | | | |
|--|--------|--------|---------|--|--|--|--|--|--|
| Operating temperature -0° C to +50° C. Complies with SANS 1156-2: 2010 | | | | | | | | | |
| PRODUCT CODE: | LPG600 | LPG800 | LPG1000 | | | | | | |
| Nominal ID mm | 6,3 | 8 | 10 | | | | | | |
| Nominal OD mm | 12 | 13 | 15 | | | | | | |
| Working Pressure Kpa | 1300 | 1200 | 1100 | | | | | | |
| Burst Pressure Kpa | 5900 | 5200 | 4500 | | | | | | |



| WATEX Air and Water Reinforced Hose – Blue and Green | | | | | | | | | | |
|--|-------|-------|--------|--|--|--|--|--|--|--|
| opaque hose for water, air lines,compressors and tyre inflating. | | | | | | | | | | |
| PRODUCT CODE: | AH600 | AH800 | AH1000 | | | | | | | |
| Nominal ID mm | 6,3 | 8 | 10 | | | | | | | |
| Nominal OD mm | 12 | 13 | 15 | | | | | | | |
| Working Pressure Kpa | 1300 | 1200 | 1100 | | | | | | | |
| Burst Pressure Kpa 5900 5200 4500 | | | | | | | | | | |



| | WATEX Oxygen BLUE and Acetylene RED Hose – for Oxy/Acetylene equipment. | | | | | | | | | | |
|--|---|------|------|-------|------|------|------|--|--|--|--|
| | vailable in 30m lengths. Made from virgin raw materials. (PR Nitrile). | | | | | | | | | | |
| PRODUCT CODE: 0XY600 0XY800 0XY1000 ACE600 ACE800 ACE100 | | | | | | | | | | | |
| | Nominal ID mm | 6,3 | 8 | 10 | 6,3 | 8 | 10 | | | | |
| d | Nominal OD mm | 12 | 13 | 15 12 | | 13 | 15 | | | | |
| I | Working Pressure Kpa | 1900 | 1800 | 1700 | 1900 | 1800 | 1700 | | | | |
| | Burst Pressure Kpa | 7600 | 7200 | 6800 | 7600 | 7200 | 6800 | | | | |



WATEX-FH Red Fire Hose. Heavy duty hose complies with SANS 1086/2007 quality procedures. Operating temperature 0° C to $+50^\circ$ C.

| PRODUCT CODE: | FH12030 | FH20030 | | | | | | |
|-----------------------------|---------|---------|--|--|--|--|--|--|
| Nominal ID (mm) | 12 | 20 | | | | | | |
| Burst Pressure Kpa | 1700 | 1500 | | | | | | |
| Working Pressure Kpa | 6800 | 6000 | | | | | | |

WATEX BUILDER'S HOSE

MADE FROM VIRGIN RAW MATERIALS WITH 5 YEAR WARRANTY. OUTER RIBBED OFFERS EXCELLENT ABRASION RESISTANCE. MINIMUM BURST PRESSURE - 2500 kPa.



- Designed for hardwearing outdoor industrial use
- 20 mm diameter in 30 m or 50 m lengths
- Professionally packaged, Shrink wrapped & Bar-coded

| WATEX BUILDER'S HOSE | 5 YEAR WARRANTY | |
|----------------------|-----------------|----------|
| PRODUCT CODE: | DLB52030 | DLB52050 |
| Nominal ID (mm) | 20 | 20 |
| Burst Pressure Kpa | 4000 | 4000 |

WATEX DRAGLINE HOSE

MANUFACTURED FROM VIRGIN RAW MATERIALS WITH 5 YEAR AND 10 YEAR WARRANTY. OUTER IS RIBBED WHICH OFFERS EXCELLENT ABRASION RESISTANCE. MINIMUM BURST PRESSURE - 2500 kPa.



| WATEX DRAGLINE HOSE | 5 YEAR WARRANTY | | | | | | | | |
|---------------------------|---------------------|-----------|----------|--|--|--|--|--|--|
| PRODUCT CODE: | DL512030 | DL5 20030 | | | | | | | |
| Nominal ID (mm) | 12 | 20 | | | | | | | |
| Burst Pressure Kpa | 4000 | 3500 | | | | | | | |
| WATEX QUALITY DRAGLII | NE 10 YEAR WARRANTY | | | | | | | | |
| PRODUCT CODE: | DL101230 | DL102030 | DL102530 | | | | | | |
| Nominal ID (mm) | 12 | 20 | 25 | | | | | | |
| Burst Pressure Kpa | 5000 | 4500 | 4000 | | | | | | |

PVC NITRILE

WATEX CROP SPRAY HOSE



|<u>|</u> |-|-

Cover Material: PVC BLUE

Liner: White, Nitrile resistant to pesticides, fertilizer.

Number of bobbins. - 1000 Den.

Liner Material:

Liner max. inside diameter. 13,20 Braid Angle - Close Liner min. inside diameter. 12,80 Max. Outer Cover thickness. 1,20 Liner max. wall thickness. 1,80 Min. Outer Cover thickness. 1,00 Liner min. wall thickness. 1,60 Weight per meter in Gms. 290 Inner Liner max. wall thickness. 1,00 Weight per 30m roll in Kgs. 8.70 Inner Liner min. wall thickness. 0,80 Min. Burst pressure - Bar. 110 Number of bobbins. - 2000 Den. Temperature Range - Degrees 24 -10 to +60

Working Pressure

Application: Pesticide orchard spraying, compressed air lines, pneumatic tools, etc.

WATEX MULTI-PURPOSE HOSE



High pressure Nitrile hose for petrol, diesel, oil, chemicals and general high pressure use. 20Bar working pressure.

24




4 000 Kpa

| WATEX MULTI-PURPO | WATEX MULTI-PURPOSE HOSE (BLACK) | | | | | | | | | | | | | | | |
|---------------------------|----------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| PRODUCT CODE: MPH | 500030 | 500100 | 600030 | 600100 | 800030 | 800100 | 100030 | 100100 | 120030 | 120100 | 160100 | 160030 | 200030 | 200100 | 250030 | 250100 |
| Nom ID (mm) | 5 | 5 | 6.3 | 6.3 | 8 | 8 | 10 | 10 | 12.5 | 12.5 | 16 | 16 | 20 | 20 | 25 | 25 |
| Burst Pressure Kpa | 7800 | 7800 | 7200 | 7200 | 7000 | 7000 | 6600 | 6600 | 6400 | 6400 | 6000 | 6000 | 6000 | 6000 | 5600 | 5600 |
| Working Pres Kpa | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 |

WATEX SUCTION HOSE: TRANSPARENT FOR BETTER VISIBILITY & MORE FLEXIBLE!

MANUFACTURED FROM VIRGIN RAW MATERIALS.



| WATEX SUCTION HOSE. Made from virgin raw materials. | | | | | | | | | | | |
|---|--------------------------------|-------------|--|--|--|--|--|--|--|--|--|
| PRODUCT CODE: | PRODUCT CODE: DESCRIPTION SIZE | | | | | | | | | | |
| SHM25030 | SUCTION HOSE YELLOW 25mm | 25mm x 30m | | | | | | | | | |
| SHM32030 | 2030 SUCTION HOSE YELLOW 32mm | | | | | | | | | | |
| SHM40030 | SUCTION HOSE YELLOW 40mm | 40mm x 30m | | | | | | | | | |
| SHM50030 | SUCTION HOSE YELLOW 50mm | 50mm x 30m | | | | | | | | | |
| SHM63030 | SUCTION HOSE YELLOW 63mm | 63mm x 30m | | | | | | | | | |
| SHM75030 | SUCTION HOSE YELLOW 75mm | 75mm x 30m | | | | | | | | | |
| SHM10030 | SUCTION HOSE YELLOW 100mm | 100mm x 30m | | | | | | | | | |
| SHM12530 | 2530 SUCTION HOSE BLACK 125mm | | | | | | | | | | |
| SHM15030 | 150mm x 30m | | | | | | | | | | |