

## FITTINGS

Our Quick-clip fittings are manufactured from UV stabilised high quality ABS plastic.



## BUILDER'S HOSE

- Designed and manufactured for hardwearing outdoor industrial use
- 20 mm diameter in lengths of 30 m or 50 m
- 5 Year design life
- Minimum Burst Pressure: 2500kPa
- Professionally packaged, shrink wrapped & Bar-coded



WATEX BUILDER'S HOSE		5 YEAR WARRANTY
PRODUCT CODE:	DLB52030	DLB52050
Nominal ID (mm)	20	20
Burst Pressure Kpa	4000	4000

## QUALITY GARDEN HOSE

- Our quality reinforced garden hose is manufactured from virgin raw material
- Hoses come in 12mm diameter as standard while some also are available in 20 mm and 25 mm diameters
- Standard length is 20m but orders can be made up to 100m
- 6 Year, 8 Year and 12 Year Warranties apply to various
- Minimum Burst Pressure is 3000kPa
- Our hoses are professionally packaged with wrap-around flap to provide information when stacked / merchandised
- For added protection and aesthetics they are also shrink wrapped
- The packaging is Bar-coded for ease of costing and stock control
- Some hose are offered with or without fittings.

**PRIVATE / PERSONAL BRANDS AVAILABLE  
SUBJECT TO MINIMUM ORDERS**

## 12YR GARDEN HOSE



- Burst pressure 3000Kpa
- Available in 12mm, 20mm and 25mm
- Available with or without hose fittings
- Available in 20, 25, 30, 50 and 100 meter lengths

## 8YR GARDEN HOSE



- Available in 3 bright colours
- Blue, Lime Green and Pink in 12mm diameter with 20metre length
- All with fittings • Burst pressure 3000Kpa

## 6YR GARDEN HOSE



- Burst pressure 2500Kpa
- Available in 12mm, 20mm and 25mm
- Available with or without hose fittings
- Available in 20, 25, 30, 50 and 100 meter lengths

# WATEX®

Since 1998

**QUALITY HOSE MANUFACTURER**

Reinforced Hosing (Pty) Ltd

Telephone: +27(11) 769 2600

Facsimile: +27(11) 769 2101

0861 661 7643

Email: info@watex.co.za

Website: www.watex.co.za

# HOSE RANGE





## SABS MINING HOSE



- Manufactured from virgin raw material



- Mining Hose is manufactured to the highest standard possible – **SANS 1086**.

WATEX Yellow/Orange/Blue/Green durable super flexible and abrasion resistant mining hose. Suitable for colder conditions. Operating temperature -10° C to +50° C. Reinforced.

PRODUCT CODE:	RM10030	RM12030	RM20030	RM25030	RM32030	RM40030	RM50030
Nominal ID (mm)	10	12	20	25	32	40	50
Burst Pressure Kpa	6800	6800	6000	5600	4000	3500	3500
Working Kpa	1700	1700	1500	1400	1000	900	900

## GAS HOSE



- QUALITY Manufactured from virgin PR NITRILE raw material
- WATEX-RMO Orange Standard Duty LPG Gas Hose (PR Nitrile).
- Operating temperature -0° C to +50° C.
- Complies with **SANS 1156-2: 2010**

WATEX-RMO Orange Standard Duty LP Gas Hose.

Operating temperature -0° C to +50° C. Complies with SANS 1156-2: 2010

PRODUCT CODE:	LPG600	LPG800	LPG1000
Nominal ID mm	6,3	8	10
Nominal OD mm	12	13	15
Working Kpa	1300	1200	1100
Burst Kpa	5900	5200	4500



## SUCTION HOSE

Made from virgin raw materials.

TRANSPARENT FOR BETTER VISIBILITY & MORE FLEXIBLE!

PRODUCT CODE	DESCRIPTION	SIZE
SHM25030	SUCTION HOSE YELLOW 25mm	25mm x 30m
SHM32030	SUCTION HOSE YELLOW 32mm	32mm x 30m
SHM40030	SUCTION HOSE YELLOW 40mm	40mm x 30m
SHM50030	SUCTION HOSE YELLOW 50mm	50mm x 30m
SHM63030	SUCTION HOSE YELLOW 63mm	63mm x 30m
SHM75030	SUCTION HOSE YELLOW 75mm	75mm x 30m
SHM10030	SUCTION HOSE YELLOW 100mm	100mm x 30m
SHM12530	SUCTION HOSE BLACK 125mm	125mm x 30m
SHM15030	SUCTION HOSE BLACK 150mm	150mm x 30m



## INDUSTRIAL TUBING

- Our clear and reinforced tubing is manufactured from virgin raw material to ensure quality



\* Refer to PVC Chemical Resistant Chart

- Clear tubing is available in thin and thick wall

- Quality manufactured for low pressure applications

- Good flexibility

- High resistance to gases and chemicals
- High pressure applications: air & oil

- From 3mm - 32mm x 30m rolls.



WATEX Clear Wall Tubing – Low pressure applications such as laboratory, instruments, fish tanks and fountain tubing.

	Chemical resistant*					Good clarity.				
Nominal ID mm	3	5	6,3	8	10	12,5	16	20	25	32
Wall Thickness										
PRODUCT CODE:	CT300	CT500	CT600	CT800	CT1000	CT1200				
CTH – Thick Wall	0,8	0,9	1	1	1,2	1,3				
PRODUCT CODE:	CTH300	CTH500	CTH600	CTH800	CTH1000	CTH1200	CTH1600	CTH2000	CTH2500	CTH3200
CTH – Thick Wall	1,4	1,5	2	2,2	2,5	2,6	2,7	2,7	3	3,1

WATEX Clear Reinforced Tubing – High pressure applications such as air, water and diluted acids and oils.

	Chemical resistant*					Good clarity.					Fish tanks and fountain tubing.				
PRODUCT CODE:	CRT300	CRT500	CRT600	CRT800	CRT1000	CRT1200	CRT1600	CRT2000	CRT2500	CRT3200					
Nominal ID mm	3	5	6,3	8	10	12,5	16	20	25	32					
Nominal OD mm	7	9	12	13	15	19	24	28	34	42					
Working Pressure Kpa	1700	1500	1300	1200	1100	1100	1000	1000	1000	900					
Burst Pressure Kpa	7000	6600	5900	5200	4500	4200	4000	4000	4000	3800					

WATEX Fuel Reinforced Hose – Transparent blue for petrol, diesel, oil and chemicals\*.

Good clarity.						
PRODUCT CODE:	CRF300	CRF500	CRF600	CRF800	CRF1000	CRF1200
Nominal ID (mm)	3	5	6,3	8	10	12,5
Nominal O D (mm)	7	9	12	13	15	19
Working Pressure Kpa	1700	1500	1300	1200	1100	1100
Burst Pressure Kpa	7000	6600	5900	5200	4500	4200

WATEX Air and Water Reinforced Hose – Blue and Green opaque hose for water, air lines, compressors and tyre inflating.

	Good clarity.				
PRODUCT CODE:			AH600	AH800	AH1000
Nominal ID mm	-	-	6,3	8	10
Nominal OD mm	-	-	12	13	15
Working Pressure Kpa	-	-	1300	1200	1100
Burst Pressure Kpa	-	-	5900	5200	4500

WATEX Oxygen BLUE and Acetylene RED Hose – for Oxy/Acetylene equipment. Available in 30m lengths. Made from virgin raw materials. (PR Nitrile).

PRODUCT CODE:	OXY600	OXY800	OXY1000	ACE600	ACE800	ACE1000
Nominal ID mm	6,3	8	10	6,3	8	10
Nominal OD mm	12	13	15	12	13	15
Working Pressure Kpa	1900	1800	1700	1900	1800	1700
Burst Pressure Kpa	7600	7200	6800	7600	7200	6800

## DRAGLINE HOSE

Manufactured from virgin raw materials with 5 year and 10 year warranty. Outer is ribbed which offers excellent abrasion resistance. Minimum burst pressure - 2500 kPa.



WATEX DRAGLINE HOSE	5 YEAR WARRANTY	
PRODUCT CODE:	DL512030	DL5 20030
Nominal ID (mm)	12	20
Burst Pressure Kpa	4000	3500



WATEX QUALITY DRAGLINE HOSE 10 YEAR WARRANTY			
PRODUCT CODE:	DL101230	DL102030	DL102530
Nominal ID (mm)	12	20	25
Burst Pressure Kpa	5000	4500	4000

## CROP SPRAY HOSE

Application: Pesticide orchard spraying, compressed air lines, pneumatic tools, etc.  
Liner: White, Nitrile resistant to pesticides, fertilizer.



Liner max. inside diameter.	13,20	Inner Liner min. wall thickness.	0,80	Min. Outer Cover thickness.	1,00	Working Pressure	4 000 Kpa
Liner min. inside diameter.	12,80	Number of bobbins. – 2000 Den.	24	Weight per meter in Gms.	290		
Liner max. wall thickness.	1,80	Number of bobbins. – 1000 Den.	24	Weight per 30m roll in Kgs.	8.70	Liner Material:	PVC NITRILE
Liner min. wall thickness.	1,60	Braid Angle - Close	C	Min. Burst pressure - Bar.	110	Cover Material:	PVC BLUE
Inner Liner max. wall thickness.	1,00	Max. Outer Cover thickness.	1,20	Temperature Range - Degrees	-10 to +60		

## WATEX MULTI-PURPOSE HOSE

WATEX MULTI-PURPOSE HOSE (BLACK) High pressure Nitrile hose for petrol, diesel, oil, chemicals and general high pressure use (20 Bar).

PRODUCT CODE: MPH	500030	500100	600030	600100	800030	800100	100030	100100	120030	120100	160100	160030	200030	200100	250030	250100
Nom ID (mm)	5	5	6,3	6,3	8	8	10	10	12,5	12,5	16	16	20	20	25	25
Burst Pressure Kpa	7800	7800	7200	7200	7000	7000	6600	6600	6400	6400	6000	6000	6000	6000	5600	5600
Working Pres Kpa	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000

